

## **DSX MKII**

## **AUTOMATIC DISTRESS SIGNAL UNIT**

The DSX alarm is specifically designed for users of breathing apparatus, and others working in potentially hazardous environments. The DSX unit will automatically emit a 96-dBA alarm should the wearer be rendered unconscious or trapped. A new concept in Distress Signal design, with many options to suit individual needs, the unit is built with the wearer in mind and will accommodate fixing to all B.A. sets.

- LOCATION FLASHES.
- CONTINUOUS MANUAL ALARM IMMEDIATE OR "TONE DELAY".
- MOVEMENT DETECTOR.
- PRE-ALARM AFTER 30 SECONDS.
- FULL ALARM 102 TO 112 LEQ (30S)Db(A)
- RED LED FLASHES WITH DISTRESS SIGNAL.
- TEMPERATURE SENSOR OPTIONAL
- **EVACUATION WHISTLE OPTIONAL.** \*
- BA DURATION TIMER OPTIONAL.
- EMC TESTED AND APPROVED. \*\*
- \* SMALL AND LOW PROFILE UNIT 119.5 x 87 x 39mm.
- VERY SECURE FIXINGS AVAILABLE FOR VERTICAL AND HORIZONTAL STRAPS.
- REMOVABLE KEY FOR TALLY BOARD ENTRY CONTROL SYSTEMS.
- LONG OPERATIONAL BATTERY LIFE.
- LOW BATTERY INDICATION AUDIO/VISUAL. \*
- MANY OPTIONAL BUILD STATES AVAILABLE.
- DESIGNED TO MEET HOME OFFICE SPECIFICATION JCDD/38.



## **SPECIFICATION**

FULL ALARM 102 to 112 Leq (30s) dB(A) OUTPUT

FREQUENCY RANGE 2.7Khz – 3.OKhz

**CAUTION FLASH** 1 FLASH EVERY 1 SEC. ALTERNATING SIDES & FRONT

MOVEMENT MONITOR PERIOD 30 SECONDS

PRE-ALARM 10 SECONDS AT 84 to 102 Leg(6s)dB(A)

**BATTERY DURACELL MN 1604** 

AUTOMODE RESET INDICATOR AMBER LED 1 SEC. FLASH ON RESET

**FULL ALARM SOUND** JCDD 38 OR S.O.S.

**BA DURATION TIMER** 5 BEEPS AT 15 MINUTES AND THEN 5 BEEPS

**EVERY 5 MINUTES THEREAFTER** 

**EVACUATION WHISTLE** JCDD 40 SPECIFICATION

SIZE 119.5 X 87 X 39mm

WEIGHT 300 GRAMS BATTERY LIFE (ON MONITOR) 157 HOURS

LOW BATTERY INDICATION 1 SEC. AUDIO TONE & RED LED EVERY 2 SEC.

**DIRECTIVE** 2004/108/EC, EN 61000-6-2(2005), EN 61000-6-3(2007) **CERTIFICATION STANDARD** EN 60079-0:2006 AND EN 60079-11:2007, EN 60529 (IP 67)

6350-99-708-9627 NSN **CERTIFICATION LEVEL** Ex II 2 G EEx ia IIC T4

**DESIGN SPECIFICATION** BS 10999:2010