Foulds Clark (London) Ltd. www.fouldsclark.co.uk



FOCO 3 FIRE HOSE

GENERAL **SPECIFICATION**

Foco 3 is a high quality fire hose for use by Professional Fire Fighters in the most demanding situations. It is constructed with an all synthetic woven textile reinforcement encased in a high tensile PVC/Nitrile reinforcement forming a unified lining and cover.

FEATURES



Oil & Chemical Resistance	Foco 3's construction and unique PVC/Nitrile rubber blend provide excellent resistance to a wide range of chemicals and oil.
Heat Resistance	Foco 3 has excellent heat resistance against accidental contact with hot embers.
Abrasion Resistance	Foco 3's strong PVC Nitrile cover provides a tough external coat ensuring excellent abrasion resistance.
Weather Resistance	Foco 3 has excellent ozone and weather resis- tance and is suitable for the most demanding environmental conditions.
Approvals	Foco 3 fully meets the requirements of the U.K. Home Office Specification JCDD 1/1 and British Standard BS6391:1983 for Type 3 hose.

TECHNICAL DATA

Internal Diameter	mm inches	25 1″	38 1 ½″	45 1 ¾″	52 2″	64 2 ½″	70 2 ¾″	75 3″	100 4″
Short Length Burst Pressure	bar	60	50	50	50	50	45	45	35
Maximum Use Pressure	bar	30	25	25	25	25	22	22	17

SHIPPING SPECIFICATION

Internal Diameter	mm	25	38	45	52	64	70	75	100
	inches	1″	1 1⁄2″	1 ¾″	2″	2 1/2″	2 3⁄4″	3″	4‴
Coil Diameter		35	38	39	41	43	44	46	50
(25 metres)	cms	33	50	59	41	45	11	40	50
Weight		210	230	280	360	500	580	640	1050
	gm/M	210	200	200	500	000	000	010	1000